

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	<b>Alloy Devil</b>
Registration number (REACH)	not relevant (mixture)
Unique formula identifier (UFI)	C47D-6YKG-A10T-QJFR
Product number	687211

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Detergent Professional use Consumer uses
--------------------------	--

#### 1.3 Details of the supplier of the safety data sheet

Maumo International BV  
Kaartenmakerstraat 4  
2984 CB Ridderkerk  
Netherlands

Telephone: +31 (0)180 699 234  
e-mail: info@maumo.nl  
Website: www.maumo.nl

#### 1.4 Emergency telephone number

Emergency information service	+31 (0)180 699 234 This number is only available during the following office hours: Mon-Fri 09:00 - 17:00
-------------------------------	--

Poison centre		
Country	Name	Telephone
Netherlands	Nationaal Vergiftigingen Informatie Centrum (UMC Utrecht) Uitsluitend bestemd om professionele hulpverleners te informeren bij acute vergiftigingen	+31 88 755 8000

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and category	Hazard statement
3.1O	acute toxicity (oral)	4	Acute Tox. 4	H302
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.4S	skin sensitisation	1	Skin Sens. 1	H317
4.1C	hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of H-phrases: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

#### 2.2 Label elements

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

### Labelling according to Regulation (EC) No 1272/2008 (CLP)

- signal word Warning

- pictograms

GHS07



- hazard statements

H302 Harmful if swallowed.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H412 Harmful to aquatic life with long lasting effects.

- precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Tactile warning of danger yes

- hazardous ingredients for labelling

Contains: 2-methylisothiazol-3(2H)-one; Sodium mercaptoacetate; 1,2-Benzisothiazol-3-(2H)-one.

### 2.3 Other hazards

Special danger of slipping by leaking/spilling product. Do not mix with other products. Do not mix with acids. Will be toxic if product comes into contact with acids.

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0,1\%$ .

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq 0,1\%$ .

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture).

### 3.2 Mixtures

The product does not contain (other) ingredients which are classified according to present knowledge of the supplier and contribute to the classification of the product and hence require reporting in this section.

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
2-(2-butoxyethoxy)ethanol	CAS No 112-34-5  EC No 203-961-6  Index No 603-096-00-8	5 - 10	Eye Irrit. 2 / H319		GHS-HC IOELV

# Safety Data Sheet





according to Regulation (EC) No. 1907/2006 (REACH)

amended by 2020/878/EU

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
	REACH Reg. No 01-2119475104-44-xxxx				
Sodium mercaptoacetate	CAS No 367-51-1  EC No 206-696-4  REACH Reg. No 01-2119968564-24-xxxx	5 – 10	Met. Corr. 1 / H290 Acute Tox. 3 / H301 Acute Tox. 4 / H312 Skin Sens. 1B / H317 Aquatic Chronic 3 / H412		
Sodium-2-ethylhexyl-sulphate	CAS No 126-92-1  EC No 204-812-8  REACH Reg. No 01-2119971586-23-xxxx	< 5	Skin Irrit. 2 / H315 Eye Dam. 1 / H318		
1,2-Benzisothiazol-3-(2H)-one	CAS No 2634-33-5  EC No 220-120-9  Index No 613-088-00-6  REACH Reg. No 01-2120761540-60-xxxx	< 5	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1 / H317 Aquatic Acute 1 / H400 Aquatic Chronic 2 / H411		GHS-HC
2-methylisothiazol-3(2H)-one	CAS No 2682-20-4  EC No 220-239-6  Index No 613-326-00-9  REACH Reg. No 01-2120764690-50-xxxx	< 5	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 2 / H330 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Skin Sens. 1A / H317 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410 EUH071		GHS-HC

**Notes**

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)  
IOELV: Substance with a community indicative occupational exposure limit value

Name of substance	Identifier	Specific Conc. Limits	M-Factors	ATE	Exposure route
Sodium mercaptoacetate	CAS No 367-51-1  EC No 206-696-4	-	-	>50 mg/kg >1.000 mg/kg	oral dermal

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

Name of sub-stance	Identifier	Specific Conc. Limits	M-Factors	ATE	Exposure route
Sodium-2-ethyl-hexylsulphate	CAS No 126-92-1  EC No 204-812-8	Eye Dam. 1; H318: C ≥ 20 % Eye Irrit. 2; H319: 10 % ≤ C < 20 %	-	-	
1,2-Benziso-thiazol-3-(2H)-one	CAS No 2634-33-5  EC No 220-120-9	Skin Sens. 1; H317: C ≥ 0,05 %	-	670 mg/kg	oral
2-methyliso-thiazol-3(2H)-one	CAS No 2682-20-4  EC No 220-239-6	Skin Sens. 1A; H317: C ≥ 0,0015 %	M-factor (acute) = 10 M-factor (chronic) = 1	120 mg/kg 242 mg/kg 0,11 mg/l/4h	oral dermal inhalation: dust/ mist

### Remarks

All the percentages given are percentages by weight unless stated otherwise. For full text of H-phrases: see SECTION 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following inhalation

Provide fresh air. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician.

#### Following skin contact

Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

#### Following eye contact

Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Induce vomiting when the affected person is not unconscious. Call a POISON CENTER/doctor.

### 4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction. May cause serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

For specialist advice physicians should contact the poison centre.

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media

Water spray; Alcohol resistant foam; Dry extinguishing powder; Carbon dioxide (CO<sub>2</sub>);  
Co-ordinate firefighting measures to the fire surroundings.

Unsuitable extinguishing media

Water jet.

#### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

During fire hazardous fumes/smoke could be produced. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Special protective equipment for firefighters

Self-contained breathing apparatus (EN 133). Standard protective clothing for firefighters.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Ventilate affected area.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Use personal protective equipment as required.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

#### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece).

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### Recommendations

- measures to prevent fire as well as aerosol and dust generation  
Use local and general ventilation. Use only in well-ventilated areas.

##### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedings.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Managing of associated risks

- flammability hazards

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge.

- incompatible substances or mixtures

Keep away from alkalis, oxidising substances, acids.

##### Control of effects

##### Protect against external exposure, such as

High temperatures. UV-radiation/sunlight.

##### Consideration of other advice

Keep only in the original container in a cool well ventilated place away from acids. Store in a closed container.

- packaging compatibilities

Keep only in original container.

#### 7.3 Specific end use(s)

There is no additional information.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### National limit values

Occupational exposure limit values (Workplace Exposure Limits)									
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Notation	Source
EU	2-(2-butoxyethoxy)ethanol	112-34-5	IOELV	10	67,5	15	101,2		2006/15/EC
NL	2-(2-butoxyethoxy)ethanol	112-34-5	GW	7,4	50	14,8	100	H	SC-SZW

##### Notation

H	absorbed through the skin
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

### Relevant DNELs/DMELs/PNECs and other threshold levels

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Sodium mercaptoacetate	367-51-1	DNEL	0,987 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Sodium mercaptoacetate	367-51-1	DNEL	0,163 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Sodium mercaptoacetate	367-51-1	DNEL	0,174 mg/m <sup>3</sup>	human, inhalatory	consumer (private households)	chronic - systemic effects
Sodium mercaptoacetate	367-51-1	DNEL	19,3 µg/kg	human, dermal	consumer (private households)	chronic - systemic effects
Sodium mercaptoacetate	367-51-1	DNEL	0,1 mg/kg bw/day	human, oral	consumer (private households)	chronic - systemic effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	67,5 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	83 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	40,5 mg/m <sup>3</sup>	human, inhalatory	consumer (private households)	chronic - systemic effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	40,5 mg/m <sup>3</sup>	human, inhalatory	consumer (private households)	chronic - local effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	60,7 mg/m <sup>3</sup>	human, inhalatory	consumer (private households)	acute - local effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	50 mg/kg bw/day	human, dermal	consumer (private households)	chronic - systemic effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	67,5 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	101,2 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	6,25 mg/kg bw/day	human, oral	consumer (private households)	chronic - systemic effects
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	DNEL	6,81 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	DNEL	0,966 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	DNEL	1,2 mg/m <sup>3</sup>	human, inhalatory	consumer (private households)	chronic - systemic effects
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	DNEL	0,345 mg/kg bw/day	human, dermal	consumer (private households)	chronic - systemic effects
2-methylisothiazol-3(2H)-one	2682-20-4	DNEL	0,021 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
2-methylisothiazol-3(2H)-one	2682-20-4	DNEL	0,043 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
2-methylisothiazol-3(2H)-one	2682-20-4	DNEL	0,021 mg/m <sup>3</sup>	human, inhalatory	consumer (private households)	chronic - local effects

## Alloy Devil

 Version number: 2.0  
 Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2-methylisothiazol-3(2H)-one	2682-20-4	DNEL	0,043 mg/m <sup>3</sup>	human, inhalatory	consumer (private households)	acute - local effects
2-methylisothiazol-3(2H)-one	2682-20-4	DNEL	0,027 mg/kg bw/day	human, oral	consumer (private households)	chronic - systemic effects
2-methylisothiazol-3(2H)-one	2682-20-4	DNEL	0,053 mg/kg bw/day	human, oral	consumer (private households)	acute - systemic effects

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Sodium mercaptoacetate	367-51-1	PNEC	0,011 mg/l	aquatic organisms	freshwater	short-term (single instance)
Sodium mercaptoacetate	367-51-1	PNEC	0,001 mg/l	aquatic organisms	marine water	short-term (single instance)
Sodium mercaptoacetate	367-51-1	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Sodium mercaptoacetate	367-51-1	PNEC	0,039 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Sodium mercaptoacetate	367-51-1	PNEC	0,004 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Sodium mercaptoacetate	367-51-1	PNEC	0,002 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	56 mg/kg	aquatic organisms	water	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	11 mg/l	aquatic organisms	water	intermittent release
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	200 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	1,1 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0,11 mg/l	aquatic organisms	marine water	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	4,4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0,44 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0,32 mg/kg	terrestrial organisms	soil	short-term (single instance)
Sodium-2-ethylhexylsulphate	126-92-1	PNEC	0,136 mg/l	aquatic organisms	freshwater	short-term (single instance)
Sodium-2-ethylhexylsulphate	126-92-1	PNEC	0,014 mg/l	aquatic organisms	marine water	short-term (single instance)
Sodium-2-ethylhexylsulphate	126-92-1	PNEC	1,35 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)



## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Sodium-2-ethylhexyl-sulphate	126-92-1	PNEC	1,5 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Sodium-2-ethylhexyl-sulphate	126-92-1	PNEC	0,15 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Sodium-2-ethylhexyl-sulphate	126-92-1	PNEC	0,22 mg/kg	terrestrial organisms	soil	short-term (single instance)
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	PNEC	4,03 µg/l	aquatic organisms	freshwater	short-term (single instance)
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	PNEC	0,403 µg/l	aquatic organisms	marine water	short-term (single instance)
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	PNEC	1,03 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	PNEC	49,9 µg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	PNEC	4,99 µg/kg	aquatic organisms	marine sediment	short-term (single instance)
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	PNEC	3 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-methylisothiazol-3(2H)-one	2682-20-4	PNEC	3,39 µg/l	aquatic organisms	freshwater	short-term (single instance)
2-methylisothiazol-3(2H)-one	2682-20-4	PNEC	3,39 µg/l	aquatic organisms	marine water	short-term (single instance)
2-methylisothiazol-3(2H)-one	2682-20-4	PNEC	0,23 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-methylisothiazol-3(2H)-one	2682-20-4	PNEC	0,047 mg/kg	terrestrial organisms	soil	short-term (single instance)

## 8.2 Exposure controls

### Appropriate engineering controls

General ventilation. Provide eyewash stations and safety showers at the workplace.

### Individual protection measures (personal protective equipment)

#### Eye/face protection



Use safety goggle with side protection (EN 166).

#### Skin protection



Protective clothing (EN 340 & EN ISO 13688).

#### Hand protection



Wear suitable gloves. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Chemical protection gloves are suitable, which are tested according to EN 374. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

- type of material

Butyl rubber

- material thickness

Use gloves with a minimum material thickness:  $\geq 0,7$  mm.

- breakthrough time of the glove material

Use gloves with a minimum breakthrough time of the glove material: >480 minutes (permeation: level 6).

- other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Full face mask/half mask/quarter mask (EN 136/140). Type: ABEK-P2 (combined filters against gases, vapours and particles, colour code: Brown/Grey/Yellow/Green/White).

Environmental exposure controls

Take appropriate precautions to avoid uncontrolled release into the environment. Keep away from drains, surface and ground water.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	liquid (viscous)
Colour	colourless
Odour	disagreeable
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	191 °C at 1.012 mbar calculated value, referring to a component of the mixture
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	LEL: UEL: not determined
Flash point	no data available
Auto-ignition temperature	210 °C (auto-ignition temperature (liquids and gases)) calculated value, referring to a component of the mixture
Decomposition temperature	no data available
pH (value)	8 – 9
Kinematic viscosity	not determined
Dynamic viscosity	2.000 – 3.000 mPa s

Solubility

Water solubility	soluble
------------------	---------

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapour pressure	0,022 mmHg at 25 °C calculated value, referring to a component of the mixture
-----------------	--

### Density and/or relative density

Density	not determined
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

### 9.2 Other information

Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant
--	---

#### Other safety characteristics

Miscibility	Completely miscible with water.
-------------	---------------------------------

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is not reactive under normal ambient conditions.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

Keep away from acids.

### 10.4 Conditions to avoid

No hazardous reaction when handled and stored according to provisions.

### 10.5 Incompatible materials

Acids, oxidisers.

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

##### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

##### Classification according to GHS (1272/2008/EC, CLP)

##### Acute toxicity

Harmful if swallowed.

- acute toxicity estimate (ATE)

Exposure route	ATE
Oral	>478,5 mg/kg

##### Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
Sodium mercaptoacetate	367-51-1	oral	>50 mg/kg
Sodium mercaptoacetate	367-51-1	dermal	>1.000 mg/kg
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	oral	670 mg/kg
2-methylisothiazol-3(2H)-one	2682-20-4	oral	120 mg/kg
2-methylisothiazol-3(2H)-one	2682-20-4	dermal	242 mg/kg
2-methylisothiazol-3(2H)-one	2682-20-4	inhalation: dust/mist	0,11 mg/4h

##### Acute toxicity of components

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Sodium mercaptoacetate	367-51-1	oral	LD50	>50 – ≤200 mg/kg	rat
Sodium mercaptoacetate	367-51-1	dermal	LD50	>1.000 – ≤2.000 mg/kg	rat
2-(2-butoxyethoxy)ethanol	112-34-5	oral	LD50	2.410 mg/kg	mouse
2-(2-butoxyethoxy)ethanol	112-34-5	dermal	LD50	2.764 mg/kg	rabbit
Sodium-2-ethylhexylsulphate	126-92-1	oral	LD50	7.570 mg/kg	rat
Sodium-2-ethylhexylsulphate	126-92-1	dermal	LD50	>2.000 mg/kg	rat
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	oral	LD50	670 mg/kg	rat
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	dermal	LD50	>2.000 mg/kg	rat
2-methylisothiazol-3(2H)-one	2682-20-4	oral	LD50	120 mg/kg	rat
2-methylisothiazol-3(2H)-one	2682-20-4	inhalation: dust/mist	LC50	0,11 mg/4h	rat
2-methylisothiazol-3(2H)-one	2682-20-4	dermal	LD50	242 mg/kg	rat

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

May cause an allergic skin reaction.

### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

Shall not be classified as carcinogenic.

### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## 11.2 Information on other hazards

### Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq 0,1\%$ .

### Other information

There is no additional information.

## SECTION 12: Ecological information

### 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Sodium mercaptoacetate	367-51-1	LC50	$>100 \text{ mg/l}$	fish	96 h
Sodium mercaptoacetate	367-51-1	EC50	$47,31 \text{ mg/l}$	aquatic invertebrates	48 h
Sodium mercaptoacetate	367-51-1	ErC50	$5,07 \text{ mg/l}$	algae	72 h
Sodium mercaptoacetate	367-51-1	NOEC	$0,54 \text{ mg/l}$	algae	72 h
2-(2-butoxyethoxy)ethanol	112-34-5	LC50	$1.300 \text{ mg/l}$	fish	96 h
2-(2-butoxyethoxy)ethanol	112-34-5	EC50	$>100 \text{ mg/l}$	aquatic invertebrates	48 h
2-(2-butoxyethoxy)ethanol	112-34-5	ErC50	$>100 \text{ mg/l}$	algae	96 h
2-(2-butoxyethoxy)ethanol	112-34-5	NOEC	$\geq 100 \text{ mg/l}$	aquatic invertebrates	48 h
Sodium-2-ethylhexylsulphate	126-92-1	LC50	$>100 \text{ mg/l}$	fish	96 h

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

amended by 2020/878/EU

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Sodium-2-ethylhexylsulphate	126-92-1	EC50	483 mg/l	aquatic invertebrates	48 h
Sodium-2-ethylhexylsulphate	126-92-1	ErC50	>511 mg/l	algae	72 h
Sodium-2-ethylhexylsulphate	126-92-1	NOEC	103 mg/l	algae	72 h
Sodium-2-ethylhexylsulphate	126-92-1	growth rate (Er-Cx) 10%	199 mg/l	algae	72 h
Sodium-2-ethylhexylsulphate	126-92-1	growth (EbCx) 10%	133 mg/l	algae	72 h
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	LC50	16,7 mg/l	fish	96 h
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	EC50	2,94 mg/l	aquatic invertebrates	48 h
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	ErC50	150 µg/l	algae	72 h
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	NOEC	55 µg/l	algae	72 h
2-methylisothiazol-3(2H)-one	2682-20-4	LC50	4,77 mg/l	fish	96 h
2-methylisothiazol-3(2H)-one	2682-20-4	EC50	1,7 mg/l	aquatic invertebrates	24 h
2-methylisothiazol-3(2H)-one	2682-20-4	ErC50	>0,072 mg/l	algae	96 h
2-methylisothiazol-3(2H)-one	2682-20-4	NOEC	1,3 mg/l	aquatic invertebrates	96 h

### Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Sodium mercaptoacetate	367-51-1	EC50	530 mg/l	microorganisms	3 h
Sodium mercaptoacetate	367-51-1	NOEC	3,9 mg/l	aquatic invertebrates	21 d
2-(2-butoxyethoxy)ethanol	112-34-5	growth (EbCx) 10%	>1.995 mg/l	microorganisms	30 min
Sodium-2-ethylhexylsulphate	126-92-1	EC50	135 mg/l	microorganisms	3 h
Sodium-2-ethylhexylsulphate	126-92-1	NOEC	≥1,357 mg/l	fish	42 d
Sodium-2-ethylhexylsulphate	126-92-1	LOEC	6,86 mg/l	aquatic invertebrates	21 d
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	EC50	13 mg/l	microorganisms	3 h
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	NOEC	11 mg/l	microorganisms	3 h
2-methylisothiazol-3(2H)-one	2682-20-4	EC50	1,4 mg/l	aquatic invertebrates	21 d
2-methylisothiazol-3(2H)-one	2682-20-4	ErC50	0,22 mg/l	algae	120 h
2-methylisothiazol-3(2H)-one	2682-20-4	LOEC	9,88 mg/l	fish	98 d
2-methylisothiazol-3(2H)-one	2682-20-4	NOEC	4,93 mg/l	fish	98 d
2-methylisothiazol-3(2H)-one	2682-20-4	growth (EbCx) 10%	1 mg/l	microorganisms	16 h

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

### 12.2 Persistence and degradability

Degradability of components					
Name of substance	CAS No	Process	Degradation rate	Time	Method
Sodium mercaptoacetate	367-51-1	oxygen depletion	84,5 %	28 d	
Sodium mercaptoacetate	367-51-1	carbon dioxide generation	>60 %	10 d	
2-(2-butoxyethoxy)ethanol	112-34-5	oxygen depletion	85 %	28 d	
Sodium-2-ethylhexylsulphate	126-92-1	carbon dioxide generation	89,3 %	28 d	
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	carbon dioxide generation	62 %	4 d	
2-methylisothiazol-3(2H)-one	2682-20-4	carbon dioxide generation	54,1 %	29 d	
2-methylisothiazol-3(2H)-one	2682-20-4	oxygen depletion	0 %	28 d	

### 12.3 Bioaccumulative potential

Bioaccumulative potential of components				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Sodium mercaptoacetate	367-51-1		-2,99 (pH value: 7, 22 °C)	
2-(2-butoxyethoxy)ethanol	112-34-5		1 (pH value: 7, 20 °C)	
Sodium-2-ethylhexylsulphate	126-92-1		-0,248 (25 °C)	
1,2-Benzisothiazol-3-(2H)-one	2634-33-5	6,62	0,63 (pH value: 7, 10 °C)	
2-methylisothiazol-3(2H)-one	2682-20-4	5,75	-0,486 (pH value: 7, 25 °C)	

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0,1\%$ .

### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq 0,1\%$ .

### 12.7 Other adverse effects

Data are not available.

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment.

Waste treatment of containers/packagings

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

### SECTION 14: Transport information

- 14.1 UN number or ID number** not subject to transport regulations
- 14.2 UN proper shipping name** not relevant
- 14.3 Transport hazard class(es)** none
- 14.4 Packing group** not assigned
- 14.5 Environmental hazards** non-environmentally hazardous acc. to the dangerous goods regulations
- 14.6 Special precautions for user**  
There is no additional information.
- 14.7 Maritime transport in bulk according to IMO instruments**  
No data available.

#### Additional information for each of the UN Model Regulations

##### **Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - additional information**

Not subject to ADR, RID and ADN.

##### **International Maritime Dangerous Goods Code (IMDG) - additional information**

Not subject to IMDG.

##### **International Civil Aviation Organization (ICAO-IATA/DGR) - additional information**

Not subject to ICAO-IATA.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### **Relevant provisions of the European Union (EU)**

##### **Restrictions according to REACH, Annex XVII**

Name	Name acc. to inventory	Restriction	No
Alloy Devil	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC	R3	3
Sodium-2-ethylhexylsulphate	substances in tattoo inks and permanent make-up	R75	75



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

amended by 2020/878/EU

## Alloy Devil

Version number: 2.0

Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

Name	Name acc. to inventory	Restriction	No
2-methylisothiazol-3(2H)-one	substances in tattoo inks and permanent make-up	R75	75
1,2-Benzisothiazol-3-(2H)-one	substances in tattoo inks and permanent make-up	R75	75
2-(2-butoxyethoxy)ethanol	2-(2-butoxyethoxy)ethanol (DEGBE)	R55	55
2-(2-butoxyethoxy)ethanol	substances in tattoo inks and permanent make-up	R75	75
Sodium mercaptoacetate	substances in tattoo inks and permanent make-up	R75	75

### Legend

R3

1. Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ash-trays,

- tricks and jokes,

- games for one or more participants, or any article intended to be used as such, even with ornamental aspects,

2. Articles not complying with paragraph 1 shall not be placed on the market.

3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:

— can be used as fuel in decorative oil lamps for supply to the general public, and

— present an aspiration hazard and are labelled with H304.

4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).

5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:

(a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage";

(b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage';

(c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.;

R55

1. Shall not be placed on the market for the first time after 27 June 2010, for supply to the general public, as a constituent of spray paints or spray cleaners in aerosol dispensers in concentrations equal to or greater than 3 % by weight.

2. Spray paints and spray cleaners in aerosol dispensers containing DEGBE and not conforming to paragraph 1 shall not be placed on the market for supply to the general public after 27 December 2010.

3. Without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that paints other than spray paints containing DEGBE in concentrations equal to or greater than 3 % by weight of that are placed on the market for supply to the general public are visibly, legibly and indelibly marked by 27 December 2010 as follows:

'Do not use in paint spraying equipment'.

## Alloy Devil

Version number: 2.0

Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

### Legend

R75

1. Shall not be placed on the market in mixtures for use for tattooing purposes, and mixtures containing any such substances shall not be used for tattooing purposes, after 4 January 2022 if the substance or substances in question is or are present in the following circumstances:

(a) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;

(b) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as reproductive toxicant category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;

(c) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin sensitiser category 1, 1A or 1B, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;

(d) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2, or as serious eye damage category 1 or eye irritant category 2, the substance is present in the mixture in a concentration equal to or greater than:

(i) 0,1 % by weight, if the substance is used solely as a pH regulator;

(ii) 0,01 % by weight, in all other cases;

(e) in the case of a substance listed in Annex II to Regulation (EC) No 1223/2009 (\*1), the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;

(f) in the case of a substance for which a condition of one or more of the following kinds is specified in column g (Product type, Body parts) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight:

(i) "Rinse-off products";

(ii) "Not to be used in products applied on mucous membranes";

(iii) "Not to be used in eye products";

(g) in the case of a substance for which a condition is specified in column h (Maximum concentration in ready for use preparation) or column i (Other) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration, or in some other way, that does not accord with the condition specified in that column;

(h) in the case of a substance listed in Appendix 13 to this Annex, the substance is present in the mixture in a concentration equal to or greater than the concentration limit specified for that substance in that Appendix.

2. For the purposes of this entry use of a mixture "for tattooing purposes" means injection or introduction of the mixture into a person's skin, mucous membrane or eyeball, by any process or procedure (including procedures commonly referred to as permanent make-up, cosmetic tattooing, micro-blading and micro-pigmentation), with the aim of making a mark or design on his or her body.

3. If a substance not listed in Appendix 13 falls within more than one of points (a) to (g) of paragraph 1, the strictest concentration limit laid down in the points in question shall apply to that substance. If a substance listed in Appendix 13 also falls within one or more of points (a) to (g) of paragraph 1, the concentration limit laid down in point (h) of paragraph 1 shall apply to that substance.

4. By way of derogation, paragraph 1 shall not apply to the following substances until 4 January 2023:

(a) Pigment Blue 15:3 (CI 74160, EC No 205-685-1, CAS No 147-14-8);

(b) Pigment Green 7 (CI 74260, EC No 215-524-7, CAS No 1328-53-6).

5. If Part 3 of Annex VI to Regulation (EC) No 1272/2008 is amended after 4 January 2021 to classify or re-classify a substance such that the substance then becomes caught by point (a), (b), (c) or (d) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the date of application of that new or revised classification is after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect on the date of application of that new or revised classification.

6. If Annex II or Annex IV to Regulation (EC) No 1223/2009 is amended after 4 January 2021 to list or change the listing of a substance such that the substance then becomes caught by point (e), (f) or (g) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the amendment takes effect after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect from the date falling 18 months after entry into force of the act by which that amendment was made.

7. Suppliers placing a mixture on the market for use for tattooing purposes shall ensure that, after 4 January 2022, the mixture is marked with the following information:

(a) the statement "Mixture for use in tattoos or permanent make-up";

(b) a reference number to uniquely identify the batch;

(c) the list of ingredients in accordance with the nomenclature established in the glossary of common ingredient names pursuant to Article 33 of Regulation (EC) No 1223/2009, or in the absence of a common ingredient name, the IUPAC name. In the absence of a common ingredient name or IUPAC name, the CAS and EC number. Ingredients shall be listed in descending order by weight or volume of the ingredients at the time of formulation. "Ingredient" means any substance added during the process of formulation and present in the mixture for use for tattooing purposes. Impurities shall not be regarded as ingredients. If the name of a substance, used as ingredient within the meaning of this entry, is already required to be stated on the label in accordance with Regulation (EC) No 1272/2008, that ingredient does not need to be marked in accordance with this Regulation;

(d) the additional statement "pH regulator" for substances falling under point (d)(i) of paragraph 1;

(e) the statement "Contains nickel. Can cause allergic reactions." if the mixture contains nickel below the concentration limit specified in Appendix 13;

(f) the statement "Contains chromium (VI). Can cause allergic reactions." if the mixture contains chromium (VI) below the concentration limit specified in Appendix 13;

(g) safety instructions for use insofar as they are not already required to be stated on the label by Regulation (EC) No 1272/2008.

The information shall be clearly visible, easily legible and marked in a way that is indelible.

The information shall be written in the official language(s) of the Member State(s) where the mixture is placed on the market, unless the Member State(s) concerned provide(s) otherwise.

Where necessary because of the size of the package, the information listed in the first subparagraph, except for point (a), shall be included instead in the instructions for use.

Before using a mixture for tattooing purposes, the person using the mixture shall provide the person undergoing the procedure with the information marked on the package or included in the instructions for use pursuant to this paragraph.

8. Mixtures that do not contain the statement "Mixture for use in tattoos or permanent make-up" shall not be used for tattooing purposes.

9. This entry does not apply to substances that are gases at temperature of 20 °C and pressure of 101,3 kPa, or generate a vapour pressure of more than 300 kPa at temperature of 50 °C, with the exception of formaldehyde (CAS No 50-00-0, EC No 200-001-8).

10. This entry does not apply to the placing on the market of a mixture for use for tattooing purposes, or to the use of a mixture for tattooing purposes, when placed on the market exclusively as a medical device or an accessory to a medical device, within the meaning of Regulation (EU) 2017/745, or when used exclusively as a medical device or an accessory to a medical device, within the same meaning.

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

### Legend

Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device, the requirements of Regulation (EU) 2017/745 and of this Regulation shall apply cumulatively.

### List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

None of the ingredients are listed.

### Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
	not assigned		

### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

None of the ingredients are listed.

### Water Framework Directive (WFD)

None of the ingredients are listed.

### Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors, amending Regulation (EC) No 1907/2006 and repealing Regulation (EU) No 98/2013

None of the ingredients are listed.

### Regulation 648/2004/EC on detergents

Labelling of contents	
Wt%	Constituents
< 5 %	anionic surfactants
	preservation agents (BENZISOTHIAZOLINONE, METHYLISOTHIAZOLINONE)

### Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

### National regulations (Netherlands)

#### SZW-lijst CMR effects

None of the ingredients are listed.

## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Indication of changes (revised safety data sheet)

Complete revision of the safety data sheet.

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
Acute Tox.	Acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

Abbr.	Descriptions of used abbreviations
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
LOEC	Lowest Observed Effect Concentration
log KOW	n-Octanol/water
Met. Corr.	Substance or mixture corrosive to metals
M-factor	Means a multiplying factor. It is applied to the concentration of a substance classified as hazardous to the aquatic environment acute category 1 or chronic category 1, and is used to derive by the summation method the classification of a mixture in which the substance is present
NLP	No-Longer Polymer
NOEC	No Observed Effect Concentration
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
SC-SZW	Staatscourant: Regeling van de Minister van Sociale Zaken en Werkgelegenheid tot wijziging van de Arbeidsomstandighedenregeling
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitisation
STEL	Short-term exposure limit
SVHC	Substance of Very High Concern
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

amended by 2020/878/EU

## Alloy Devil

Version number: 2.0  
Replaces version of: 12.10.2023 (1)

Revision: 26.03.2024

**List of relevant phrases (code and full text as stated in section 2 and 3)**

Code	Text
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.